

DECLARATION OF PERFORMANCE

No.: 15/2026

1. **Product name (ID code):** PolTherma TS X 40 PIR L, M, SM, P, SP25
2. **Intended use:** external walls, internal walls
3. **Manufacturer:** Europanel Sp. z o.o., Inflancka 5/81, 00-189 Warszawa, production plant: Latkowo 35, 88-100 Inowrocław
4. **Authorised representative:** N/A
5. **Systems of assessment and verification of constancy:** Fire parameters System 3, other parameters System 4
6. **Harmonised standard:** EN 14509:2013

Notified bodies:

Instytut Techniki Budowlanej Warszawa, accreditation no.: AB 023, notification no.: 1488

Certbud Sp. z o.o. Warszawa, accreditation no.: AB 1596, notification no.: NB 2310

FireLab Sp. z o.o. Warszawa, accreditation no.: AB 1777, notification no.: 2904

Fires s.r.o. Batizovce, notification no.: 1396

7. Declared performance properties:

Basic characteristics	Declared value	Technical specification
Thermal insulation	PUR (rigid polyurethane foam PIR type); Density: 38 +/-3 kg/m³; Thickness: 40 mm	EN 14509:2013
Heat transfer $U_{d,s}$	0,57 W/m²K	
Thermal conductivity $\lambda_{declared}$	0,022 W/mK	
Tensile strength	0,06 MPa	
Shear strength	0,098 MPa	
Shear modulus (core)	2,65 MPa	
Compressive strength (core)	0,1 MPa	
Creep coefficient	t=2000 h: 2,74; t=100 000 h: 3,43	
Bending resistance in span		
- positive bending	2,55 kNm/m	
- positive bending, elevated temp.	2,47 kNm/m	
- negative bending	2,64 kNm/m	
- negative bending elevated temp.	2,56 kNm/m	
Bending resistance at an internal support		
- positive bending	2,31 kNm/m	
- positive bending, elevated temp.	2,24 kNm/m	
- negative bending	2,21 kNm/m	
- negative bending elevated temp.	2,14 kNm/m	
Water permeability	Class A (1200 Pa)	
Air permeability	$\leq 0,1 \text{ m}^3/\text{h}/\text{m}^2$	
Water vapour permeability	Fulfil, impermeable	
Proper acoustic insulation	Rw 26 (-3, -4) dB	
Sound absorption	$\alpha_w = 0,15$	
Concentrated load resistance	NPD	
Durability	Fulfil	
Hazardous substances	NPD	
External facing	steel 0,5 mm; S280GD; Z225 or AZ120 or ZM100; Top coat SP25	EN 10346:2015 EN 10143:2008
Internal facing	steel 0,5 mm; S280GD; Z225 or AZ120 or ZM100; Top coat SP25	EN 10346:2015 EN 10143:2008
Reaction to fire (core)	E	EN 13501-1:2018
Reaction to fire (product)	B-s1,d0	EN 13501-1:2019
Fire resistance	NPD	EN 13501-2:2023

8. Appropriate technical documentation or special technical documentation: N/A

The performance of the product specified above is in accordance with the set of declared performance characteristics. This declaration of performance is issued in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer specified above.

On behalf of the manufacturer: Janusz Szczepański, Warszawa, July 1st 2026

EUROPANELS

Spółka z o.o.

00-189 Warszawa, ul. Inflancka 5 lok. 81

NIP 525-24-63-541

PROKURENT
Janusz Szczepański