



13	300	350	–	–	0.5	424	1250; 2000; 2500	1.66
12	250	300	–	–	0.5	374	1250; 2000; 2500	1.47
11	200	250	–	–	0.5	324	1250; 2000; 2500	1.27
10	160	210	–	–	0.5	284	1250; 2000; 2500	1.11
9	150	200	–	–	0.5	274	1250; 2000; 2500	1.08
8	125	175	–	–	0.5	249	1250; 2000; 2500	0.98
7	120	170	–	–	0.5	244	1250; 2000; 2500	0.96
6	100	150	–	–	0.5	224	1250; 2000; 2500	0.88
5	80	130	–	–	0.5	204	1250; 2000; 2500	0.80
4	75	125	–	–	0.5	199	1250; 2000; 2500	0.78
3	60	110	–	–	0.5	184	1250; 2000; 2500	0.72
2	50	100	–	–	0.5	174	1250; 2000; 2500	0.68
1	40	90	–	–	0.5	164	1250; 2000; 2500	0.64
LP	Panel thickness [mm]	A [mm]	B [mm]	K [°]	Steel thickness [mm]	width of steel [mm]	length [mm]	weight [kg/mb]

Project	–
	–

Content	Flashing 002 External corner unsymmetrical
---------	---

designed by	Europanel	Date	2010.07.25
-------------	-----------	------	------------

drawing no.	21–02	Change	A
-------------	-------	--------	---



scale	1:1
-------	-----

file	21–02.dwg
------	-----------

The designer makes the final decision regarding using the specific solution