



12	300	300	-	-	0.5	412	1250; 2000; 2500	1.62
11	250	250	-	-	0.5	362	1250; 2000; 2500	1.42
10	200	200	-	-	0.5	312	1250; 2000; 2500	1.22
9	150	150	-	-	0.5	262	1250; 2000; 2500	1.03
8	125	125	-	-	0.5	237	1250; 2000; 2500	0.93
7	120	120	-	-	0.5	232	1250; 2000; 2500	0.91
6	100	100	-	-	0.5	212	1250; 2000; 2500	0.83
5	80	80	-	-	0.5	192	1250; 2000; 2500	0.75
4	75	75	-	-	0.5	187	1250; 2000; 2500	0.73
3	60	60	-	-	0.5	172	1250; 2000; 2500	0.68
2	50	50	-	-	0.5	162	1250; 2000; 2500	0.64
1	40	40	-	-	0.5	152	1250; 2000; 2500	0.60
Pos. Nr.	Plattenstärke D [mm]	A [mm]	B [mm]	K [°]	Blechstärke [mm]	Abwicklung [mm]	Längen [mm]	Gewicht [kg/mb]

Projekt	-
---------	---

Inhalt	Kantprofil 009 C-Profil
--------	----------------------------



Bearbeitet von	Europanel
----------------	-----------

Datum	2010.07.25
-------	------------

Maßstab	1:1
---------	-----

Nr. der Zeichnung	21-09
-------------------	-------

Änderung	A
----------	---

Datei	21-09.dwg
-------	-----------

Die endgültige Entscheidung für die Auswahl und die Details zur konkreten Ausführung der Konstruktion wird von dem Projektanten getroffen.