



13	300	355	-	-	0.5	1184	1250; 2000; 2500	4.65
12	250	305	-	-	0.5	1084	1250; 2000; 2500	4.25
11	200	255	-	-	0.5	984	1250; 2000; 2500	3.86
10	160	215	-	-	0.5	904	1250; 2000; 2500	3.55
9	150	205	-	-	0.5	884	1250; 2000; 2500	3.47
8	125	180	-	-	0.5	834	1250; 2000; 2500	3.27
7	120	175	-	-	0.5	824	1250; 2000; 2500	3.23
6	100	155	-	-	0.5	784	1250; 2000; 2500	3.08
5	80	135	-	-	0.5	744	1250; 2000; 2500	2.92
4	75	130	-	-	0.5	734	1250; 2000; 2500	2.88
3	60	115	-	-	0.5	704	1250; 2000; 2500	2.76
2	50	105	-	-	0.5	684	1250; 2000; 2500	2.68
1	40	95	-	-	0.5	664	1250; 2000; 2500	2.61
LP	Grubość płyty D [mm]	A [mm]	B [mm]	K [°]	Grubość blachy [mm]	Rozwinięcie [mm]	Długości [mm]	Masa obróbki [kg/mb]

Projekt	-
---------	---

Zawartość	Obróbka 016 Kątownik zewnętrzny rowkowany
-----------	--



Opracował	EUROPANELS
-----------	------------

Data	2021.03.31
------	------------

Skala	1:2
-------	-----

Numer rys.	21-16
------------	-------

Zmiana	A
--------	---

Plik	21-16.pdf
------	-----------

Ostateczną decyzję w sprawie wyboru i szczegółów konkretnych rozwiązań konstrukcyjnych podejmuje projektant