



13	300	342	-	-	0.5	996	1250; 2000; 2500	3.91
12	250	292	-	-	0.5	896	1250; 2000; 2500	3.52
11	200	242	-	-	0.5	796	1250; 2000; 2500	3.12
10	160	202	-	-	0.5	716	1250; 2000; 2500	2.81
9	150	192	-	-	0.5	696	1250; 2000; 2500	2.73
8	125	167	-	-	0.5	646	1250; 2000; 2500	2.54
7	120	162	-	-	0.5	636	1250; 2000; 2500	2.50
6	100	142	-	-	0.5	596	1250; 2000; 2500	2.34
5	80	122	-	-	0.5	556	1250; 2000; 2500	2.18
4	75	117	-	-	0.5	546	1250; 2000; 2500	2.14
3	60	102	-	-	0.5	516	1250; 2000; 2500	2.02
2	50	92	-	-	0.5	496	1250; 2000; 2500	1.95
1	40	82	-	-	0.5	476	1250; 2000; 2500	1.87
LP	Grubość płyty D [mm]	A [mm]	B [mm]	K [°]	Grubość blachy [mm]	Rozwinięcie [mm]	Długości [mm]	Masa obróbki [kg/mb]

Projekt	-
	-

Zawartość	Obróbka 018 Kątownik zewnętrzny kasetonowy
-----------	---

Opracował	EUROPANELS	Data	2021.03.31
-----------	------------	------	------------

Numer rys.	21-18	Zmiana	A
------------	-------	--------	---



Skala	1:2
-------	-----

Plik	21-18.pdf
------	-----------

Ostateczną decyzję w sprawie wyboru i szczegółów konkretnych rozwiązań konstrukcyjnych podejmuje projektant