




13	300	420	-	-	0.5	952	1250; 2000; 2500	3.74
12	250	370	-	-	0.5	852	1250; 2000; 2500	3.34
11	200	320	-	-	0.5	751	1250; 2000; 2500	2.95
10	160	280	-	-	0.5	672	1250; 2000; 2500	2.64
9	150	270	-	-	0.5	652	1250; 2000; 2500	2.56
8	125	245	-	-	0.5	602	1250; 2000; 2500	2.36
7	120	240	-	-	0.5	592	1250; 2000; 2500	2.32
6	100	220	-	-	0.5	562	1250; 2000; 2500	2.17
5	80	200	-	-	0.5	512	1250; 2000; 2500	2.01
4	75	195	-	-	0.5	502	1250; 2000; 2500	1.97
3	60	180	-	-	0.5	472	1250; 2000; 2500	1.85
2	50	170	-	-	0.5	452	1250; 2000; 2500	1.77
1	40	160	-	-	0.5	432	1250; 2000; 2500	1.70
LP	Panel thickness D [mm]	A [mm]	B [mm]	K [°]	Steel thickness [mm]	Width of steel [mm]	Length [mm]	Weight [kg/mb]

Project	-
---------	---

Content	Flashing 020 External corner- flat
---------	---------------------------------------

Designed by	Europanel	Date	2011.04.20
-------------	-----------	------	------------

Drawing no.	21-20	Change	A
-------------	-------	--------	---



Scale	1:2
-------	-----

File	21-20.dwg
------	-----------

The designer makes the final decision regarding using the specific solution