



12	300	300	-	-	0.5	660	1250; 2000; 2500	2.59
11	250	250	-	-	0.5	610	1250; 2000; 2500	2.39
10	200	200	-	-	0.5	560	1250; 2000; 2500	2.20
9	150	150	-	-	0.5	510	1250; 2000; 2500	2.00
8	125	125	-	-	0.5	485	1250; 2000; 2500	1.90
7	120	120	-	-	0.5	480	1250; 2000; 2500	1.88
6	100	100	-	-	0.5	460	1250; 2000; 2500	1.80
5	80	80	-	-	0.5	440	1250; 2000; 2500	1.73
4	75	75	-	-	0.5	435	1250; 2000; 2500	1.71
3	60	60	-	-	0.5	420	1250; 2000; 2500	1.65
2	50	50	-	-	0.5	410	1250; 2000; 2500	1.61
1	40	40	-	-	0.5	400	1250; 2000; 2500	1.57
LP	Plattenstärke D [mm]	A [mm]	B [mm]	K [°]	Blechstärke [mm]	Abwicklung [mm]	Längen [mm]	Gewicht [kg/mb]

Projekt	-
---------	---

Inhalt	Kantprofil 024 Ortgangprofil
--------	---------------------------------

Bearbeitet von	Europanel
----------------	-----------

Datum	2011.04.20
-------	------------

Nr. der Zeichnung	21-24
-------------------	-------

Änderung	A
----------	---



Maßstab	1:2
---------	-----

Datei	21-24.dwg
-------	-----------

Die endgültige Entscheidung für die Auswahl und die Details zur konkreten Ausführung der Konstruktion wird von dem Projektanten getroffen.