



12	300	300	-	-	0.5	660	1250; 2000; 2500	2.59
11	250	250	-	-	0.5	610	1250; 2000; 2500	2.39
10	200	200	-	-	0.5	560	1250; 2000; 2500	2.20
9	150	150	-	-	0.5	510	1250; 2000; 2500	2.00
8	125	125	-	-	0.5	485	1250; 2000; 2500	1.90
7	120	120	-	-	0.5	480	1250; 2000; 2500	1.88
6	100	100	-	-	0.5	460	1250; 2000; 2500	1.80
5	80	80	-	-	0.5	440	1250; 2000; 2500	1.73
4	75	75	-	-	0.5	435	1250; 2000; 2500	1.71
3	60	60	-	-	0.5	420	1250; 2000; 2500	1.65
2	50	50	-	-	0.5	410	1250; 2000; 2500	1.61
1	40	40	-	-	0.5	400	1250; 2000; 2500	1.57
LP	Grubość płyty D [mm]	A [mm]	B [mm]	K [°]	Grubość blachy [mm]	Rozwinięcie [mm]	Długości [mm]	Masa obróbki [kg/mb]

Projekt	-
---------	---

Zawartość	Obróbka 024 Listwa zamykająca
-----------	----------------------------------

Opracował	Włozamot	Data	2011.04.20
-----------	----------	------	------------

Numer rys.	21-24	Zmiana	A
------------	-------	--------	---



Skala	1:2
-------	-----

Plik	21-24.pdf
------	-----------

Ostateczną decyzję w sprawie wyboru i szczegółów konkretnych rozwiązań konstrukcyjnych podejmuje projektant