



| | | | | | | | | |
|----|-------------------------|-----------|-----------|----------|------------------------|---------------------|------------------|-------------------------|
| 14 | 300 | 300 | 50 | - | 0.5 | 660 | 1250; 2000; 2500 | 2.59 |
| 13 | 250 | 250 | 50 | - | 0.5 | 610 | 1250; 2000; 2500 | 2.39 |
| 12 | 200 | 200 | 50 | - | 0.5 | 560 | 1250; 2000; 2500 | 2.20 |
| 11 | 165 | 165 | 50 | - | 0.5 | 525 | 1250; 2000; 2500 | 2.06 |
| 10 | 150 | 150 | 50 | - | 0.5 | 510 | 1250; 2000; 2500 | 2.00 |
| 9 | 145 | 145 | 50 | - | 0.5 | 505 | 1250; 2000; 2500 | 1.98 |
| 8 | 125 | 125 | 50 | - | 0.5 | 485 | 1250; 2000; 2500 | 1.90 |
| 7 | 120 | 120 | 50 | - | 0.5 | 480 | 1250; 2000; 2500 | 1.88 |
| 6 | 100 | 100 | 50 | - | 0.5 | 460 | 1250; 2000; 2500 | 1.80 |
| 5 | 80 | 80 | 50 | - | 0.5 | 440 | 1250; 2000; 2500 | 1.73 |
| 4 | 75 | 75 | 50 | - | 0.5 | 435 | 1250; 2000; 2500 | 1.71 |
| 3 | 60 | 60 | 47 | - | 0.5 | 417 | 1250; 2000; 2500 | 1.64 |
| 2 | 50 | 50 | 50 | - | 0.5 | 410 | 1250; 2000; 2500 | 1.61 |
| 1 | 40 | 40 | 50 | - | 0.5 | 400 | 1250; 2000; 2500 | 1.57 |
| LP | Grubość płyty D [mm] | A [mm] | B [mm] | K [°] | Grubość blachy [mm] | Rozwinięcie [mm] | Długości [mm] | Masa obróbki [kg/mb] |

| | |
|---------|---|
| Projekt | - |
|---------|---|

| | |
|-----------|----------------------------------|
| Zawartość | Obróbka 024 Listwa zamykająca |
|-----------|----------------------------------|

| | |
|-----------|------------|
| Opracował | EUROPANELS |
|-----------|------------|

| | |
|------|------------|
| Data | 2021.03.31 |
|------|------------|



| | |
|-------|-----|
| Skala | 1:2 |
|-------|-----|

| | |
|------------|-------|
| Numer rys. | 21-24 |
|------------|-------|

| | |
|--------|---|
| Zmiana | A |
|--------|---|

| | |
|------|-----------|
| Plik | 21-24.pdf |
|------|-----------|

Ostateczną decyzję w sprawie wyboru i szczegółów konkretnych rozwiązań konstrukcyjnych podejmuje projektant